


XNA Series

18 – 26GHz Low Noise Amplifier

Features

- Frequency Range: 18 - 26GHz
- Gain: 41dB min.
- P_{1dB}: +19dBm min.
- IP3: +32dBm typ.
- Noise Figure: 2.4dB max.
- DC Power: 15V @ 275mA
- Field Replaceable SMA-F

Photo



Description

XNA-18002600-241941 is a high performance Microwave Low Noise Amplifier, with standard frequency range of 18 to 26GHz.

Electrical Specifications @+25 °C, Z_{in}=Z_{out}=50 Ω, V_{supply} = +15VDC







Parameter	Unit	Minimum	Typical	Maximum
Frequency Range	GHz	18		26
Gain (S21)	dB	41	43	
Gain Flatness	dB		±1.0	±1.5
Output Power P _{1dB}	dBm	+19		
Output Third Order Intercept IP3	dBm		+32	
Noise Figure	dB			2.4
Isolation S12	dB		-65	
VSWR-Input (S11)	ratio			2.0:1
VSWR-Output (S22)	(unitless)			2.5:1
DC Power Supply - voltage	V	12	15	
DC Power Supply - current	mA		225	275
Operating Temperature	°C	-54		+85
Size (RF/DC feedthru's excluded)	Inch/mm	0.64 x 0.70 x 0.29/16.25 x 17.78 x 7.37 (LxWxH)		
Weight	Oz	0.35 (10 grams)		

WARNING: MUST USE HEAT SINK IF CASE TEMPERATURE EXCEEDS 50 °C

XNA Series

18 – 26GHz Low Noise Amplifier

Typical Performance @ +25 °C



XNA Series

18 – 26GHz Low Noise Amplifier

Absolute Maximum Ratings

Parameter	Absolute Maximum
RF Input Power	+15dBm
Supply Voltage (Survival)	+16V
Operating Temperature	-54 °C to +85 °C
Storage Temperature	-55 °C to +125 °C

Outline

