


FMR Series

450-600MHz Input Frequency Tripler

Features

- Input Frequency: 450 – 600MHz
- Output Frequency: 1350 – 1800MHz
- Conversion Gain: 9dB
- F0 Isolation: 35dB
- Input Drive Level: -3dBm
- DC Power: 12V
- SMA Connector

Picture



Performance@530MHz, Pin= -3dBm

Description







FMR-3-3 is an active frequency tripler operates with input frequency range from 450 to 600MHz and output frequency range from 1350 to 1800MHz.

Electrical Specifications @ +25 °C, $Z_S = Z_L = 50$ Ohms, Pin = -3dBm

Parameter	Unit	Min.	Typ.	Max.
Input Frequency Range	MHz	450		600
Output Frequency Range	MHz	1350		1800
Conversion Gain	dB	5	9	11
F ₀ Isolation *	dB		35	
2F ₀ Isolation *	dB		30	
4F ₀ Isolation *	dB		40	
VSWR Input			1:1.35	
Output			1:3.00	
DC Power Input	V	10	12	15
Operating Current	mA		105	

* Isolation with respect to output power level


Typical Performance @ +25 °C



Absolute Maximum Ratings

Parameter	Absolute Maximum
RF Input Power	+23dBm
Operating Temperature	-40 °C to +85 °C
Storage Temperature	-55 °C to +105 °C

Outline



	A	B	C	D	E	F	G	H	I	J
Inch	1.250	1.250	0.563	0.450	1.000	0.625	1.000	0.250	0.500	0.187
mm	31.75	31.75	14.29	11.43	25.40	15.88	25.40	6.35	12.70	4.76