

LNA Series

1150 – 1300MHz Low Noise Amplifier

Features

- Frequency Range: 1150-1300MHz
- Gain: 20dB
- P_{1dB}: +12dBm
- IP3: +24dBm
- Noise Figure: 1.2dB
- DC Power: 6 - 24V
- SMA Connector

Performance measured @ 1200MHz

Description

LNA-1200 is a 1.2dB Noise Figure Low Noise Amplifier operates with frequency range usable from 1150 to 1300MHz.







Picture



Electrical Specifications @ +25 °C

Parameter	Unit	Minimum	Typical	Maximum
Frequency Range	MHz	1150		1300
Gain f = 1150MHz	dB		22	
f = 1200MHz	dB	19	21	
f = 1300MHz	dB		20	
P _{1dB} f = 1200MHz	dBm		+12	
IP3 f= 1200MHz	dBm		+24	
Noise Figure	dB		1.2	1.3
Reverse Isolation	dB		-28	
VSWR f = 1200MHz				
Input VSWR			2.0:1	
Output VSWR			1.6:1	
DC Power Supply	V	6	12	24
Supply Current	mA		25	


Typical Performance @ +25 °C



Absolute Maximum Ratings

Parameter	Absolute Maximum
RF Input Power	+15dBm
Supply Voltage	+25V
Operating Temperature	-40 °C to +85 °C
Storage Temperature	-55 °C to +125 °C

Outline



	A	B	C	D	E	F	G	H	I	J
Inch	1.250	1.250	0.563	0.450	1.000	0.625	1.000	0.250	0.500	0.187
mm	31.75	31.75	14.29	11.43	25.40	15.88	25.40	6.35	12.70	4.76